

SXS702 24 Volt 7 kW 11Th/CW

New

To suit: Hino Applications
Engine: EK200 Diesel

Dry Clutch

Overall Length	Mounting Hole Dia.	Mt Holes Cnt. to Cnt.	Flange Dia.	Pinion Dia.	Pinion at Rest
397mm	15mm	178 x 166 x 120mm	122mm	47mm	43mm



SXS706 24 Volt 5.5 kW 11Th/CW

New

To suit: Hino P-FD16, P-FD17
Engine: HO6C, HO7C Diesel

Dry Clutch

Overall Length	Mounting Hole Dia.	Mt Holes Cnt. to Cnt.	Flange Dia.	Pinion Dia.	Pinion at Rest
379mm	13mm	141 x 120 x 107mm	100mm	40mm	28mm



SXS708 24 Volt 7 kW 11Th/CW

New

To suit: Hino FS, FN, FR
Engine: EK100 Diesel, 13.3L

Dry Clutch

Overall Length	Mounting Hole Dia.	Mt Holes Cnt. to Cnt.	Flange Dia.	Pinion Dia.	Pinion at Rest
390mm	15mm	178 x 165 x 120mm	122mm	48mm	42mm



SXS709 24 Volt 4.5 kW 11Th/CW

New

To suit: Hino FT, FD, FC
Engine: 6.0L W06E Diesel

Dry Clutch

Overall Length	Mounting Hole Dia.	Mt Holes Cnt. to Cnt.	Flange Dia.	Pinion Dia.	Pinion at Rest
345mm	15mm	152mm	105mm	40mm	31mm



SXS713 24 Volt 4.5 kW 11Th/CW

New

To suit: Hino Ranger, Dutro
Engine: J08C/J05C
Will replace unit without Nose Cone

Dry Clutch

Overall Length	Mounting Hole Dia.	Mt Holes Cnt. to Cnt.	Flange Dia.	Pinion Dia.	Pinion at Rest
290mm	15mm / M14	140mm	105mm	40mm	31mm



SXS714 24 Volt 6.0kW 11Th/CW

New

To suit: Nissan UD TW, TZA
Engine: REB8, RF8

Dry Clutch

Overall Length	Mounting Hole Dia.	Mt Holes Cnt. to Cnt.	Flange Dia.	Pinion Dia.	Pinion at Rest
390mm	15.5mm	156 x 146 x 104mm	122mm	47.5mm	40.5mm



SXS715 24 Volt 5.5 kW 11Th/CW

New

To suit: Hino FD, FF
Engine: EH500, EH700, HO6C Turbo Diesel

Dry Clutch

Overall Length	Mounting Hole Dia.	Mt Holes Cnt. to Cnt.	Flange Dia.	Pinion Dia.	Pinion at Rest
328mm	13mm	140 x 120 x 107mm	100mm	40mm	25mm



SXS9800 24 Volt 5 kW 11Th/CW

New

To suit: Hino FT, FD, FC
Engine: W06

Dry Clutch
For Wet Clutch use DRX72010

Overall Length	Mounting Hole Dia.	Mt Holes Cnt. to Cnt.	Flange Dia.	Pinion Dia.	Pinion at Rest
295mm	14mm	152mm	105mm	40mm	31mm



SXS9801 24 Volt 4.5 kW 11Th/CW

New

To suit: Hino Ranger, FB112, FC112
Engine: W04D

Dry Clutch
For Wet Clutch use DRX72010

Overall Length	Mounting Hole Dia.	Mt Holes Cnt. to Cnt.	Flange Dia.	Pinion Dia.	Pinion at Rest
285mm	14 / 15mm	158mm	105mm	40mm	30mm



SXS9802 24 Volt 6 kW 11Th/CW

New

To suit: Hino GS224
Engine: 9.4L EM100, EP100

Dry Clutch
For Wet Clutch use DRX72010

Overall Length	Mounting Hole Dia.	Mt Holes Cnt. to Cnt.	Flange Dia.	Pinion Dia.	Pinion at Rest
330mm	16mm	178 x 166 x 120mm	121mm	47mm	42mm



To suit Sawafuji

To suit Sawafuji

SXS9803 24 Volt 6 kW 11Th/CW

New

To suit: Hino FN270, FN272
Engine: 13.3L EK100

Dry Clutch

Overall Length	Mounting Hole Dia.	Mt Holes Cnt. to Cnt.	Flange Dia.	Pinion Dia.	Pinion at Rest
330mm	15mm	178 x 165 x 120mm	121mm	43mm	42mm




SXS9805 24 Volt 6kW 11Th/CW

New

To suit: Hino Applications
Engine:

Dry Clutch

Overall Length	Mounting Hole Dia.	Mt Holes Cnt. to Cnt.	Flange Dia.	Pinion Dia.	Pinion at Rest



SXS9806 24 Volt 6kW 11Th/CW

New

To suit: Hino Applications
Engine:

Dry Clutch

Overall Length	Mounting Hole Dia.	Mt Holes Cnt. to Cnt.	Flange Dia.	Pinion Dia.	Pinion at Rest

SXS9807 24 Volt 6kW 11Th/CW

New

To suit: Hino Applications
Engine:

Dry Clutch

Overall Length	Mounting Hole Dia.	Mt Holes Cnt. to Cnt.	Flange Dia.	Pinion Dia.	Pinion at Rest

SXS9808 24 Volt 6kW 11Th/CW

New

To suit: Hino Applications
Engine:

Dry Clutch

Overall Length	Mounting Hole Dia.	Mt Holes Cnt. to Cnt.	Flange Dia.	Pinion Dia.	Pinion at Rest

To suit Sawafuji